

11



Bridge Balance Resistors & Bondable Terminals

Resistor Pattern	Resistance in OHMS	Resistor types	Dimensions in mm					
			Active Gauge Length	Active Gauge Width	Overall Length	Overall Width	Matrix Length	Matrix Width
Balco 	17	5/17/PB	3.10	2.70	6.00	3.20	7.20	4.5
	18	5/18/PB	3.10	2.70	6.00	3.20	7.20	4.5
	19	5/19/PB	3.10	2.70	6.00	3.20	7.20	4.5
	20	5/20/PB	3.10	2.70	6.00	3.20	7.20	4.5
	21	5/21/PB	3.10	2.70	6.00	3.20	7.20	4.5
	22	5/22/PB	3.10	2.70	6.00	3.20	7.20	4.5
	23	5/23/PB	3.10	2.70	6.00	3.20	7.20	4.5
	24	5/24/PB	3.10	2.70	6.00	3.20	7.20	4.5
	28	5/28/PB	3.10	2.70	6.00	3.20	7.20	4.5
	30	5/30/PB	3.10	2.70	6.00	3.20	7.20	4.5
	32	5/32/PB	3.10	2.70	6.00	3.20	7.20	4.5

Apex Resistor	Resistance in OHMS	Resistor types	Active Gauge Length	Active Gauge Width	Overall Length	Overall Width
	0.8 to 4.5 ± 15%	APEX - C (CONSTANTAN)	8.00	4.50	10.00	6.50
	0.7 to 3.5 ± 15%	APEX - B (BALCO)	8.00	4.50	10.00	6.50

Bondable Terminals	Part Number	Size Not to Scale	Terminal Length	Terminal Width	Terminal Spacing	Matrix Width	Quantity per pack
	SBT - 1		1.61	0.65	0.46	10.10	70 STRIPS
	SBT - 2		2.38	0.96	0.64	16.35	60 STRIPS
	SBT - 3		3.17	1.29	0.67	21.79	50 STRIPS
	SBT - 4		4.78	1.97	1.32	32.67	40 STRIPS
	SBT - 5		6.36	2.58	1.77	43.87	30 STRIPS
	SBT - 6		9.53	3.95	2.68	65.50	20 STRIPS

Tel: 01265 55734



Fax: 01265 58195