









Dual Element Strain Gauges



Gauge Pattern	Resistance in OHMS	Gauge Types Available	Dimensions in mm					
			Active Gauge Length	Active Gauge Width	Overall Length	Overall Width	Matrix Length	Matrix Width
2/1000/D 	1000 : 0.15% each element	2/1000/PC/D 2/1000/EC/D	2.10	3.00 each	4.50	6.40	9.00	10.00
3S/350/D 	350 : 0.15% each element	3S/350/PC/D 3S/350/EC/D	3.10	1.70 each	5.60	3.70	7.00	6.00
3/1000/D 	1000 : 0.15% each element	3/1000/PC/D 3/1000/EC/D	3.00	2.80 each	6.00	6.40	10.00	10.00
6/350/D 	350 : 0.15% each element	6/350/PC/D 6/350/EC/D	5.20	3.10 each	8.40	7.30	14.00	11.00
7N/350/D 	350 : 0.15% each element	7N/350/PC/D 7N/350/EC/D	6.30	2.80 each	9.20	6.10	12.50	9.50
7/1000/D 	1000 : 0.15% each element	7/1000/PC/D 7/1000/EC/D	6.40	3.00 each	10.00	6.70	13.00	11.00
7/2250/D 	2250 : 0.15% each element	7/2250/PC/D 7/2250/EC/D	6.40	6.40 each	10.00	6.50	12.00	8.50
8/350/D 	350 : 0.15% each element	8/350/PC/D 8/350/EC/D	6.60	3.40 each	10.00	7.70	13.60	9.70

Tel: 01265 55734



Fax: 01265 58195